

MAX

BUILDING OUR WORLD

SuperSider

CN565S3

Drives 1-1/2" to 2-1/2" flat wire welded nails
Drives 1-1/4" to 2-1/2" flat plastic sheet collated n nails



FEATURES


● Easy twist adjustable exhaust deflector

Exhaust air can easily be diverted 360 away from user without any tool.



● Slim guide contact arm prevents from the wire scrap flying

There is no space between nose and contact arm and slim guide contact arm can guide the nail to the end




● New improved removable contact nose

Upgraded contact nose that is removable and designed with a larger inside diameter to accommodate larger nail heads, for easy jam clearance and to prevent accidental detachment.

● Slim guide contact arm doesn't highlight the driver mark



● Anti-double fire mechanism (US Patent 5597106)




● A rafter hook is installed on the tool



● Dial adjustable depth control



● Maintenance free end cap filter (US Patent 5637125)



● Easy-load magazine



It prevents foreign substances from entering the tool. Internal parts last longer and the inside of the tool is kept clean. The filter has a selfcleaning feature; foreign substances are ejected automatically from the tool when the air hose is disconnected.



APPLICATIONS

- Siding
- Fencing
- Exterior trim
- Sheathing
- Subfloors
- Roof decking
- Exterior deck
- Furring
- Strapping

TOOL SPECIFICATIONS

MODEL	CN565S3
WEIGHT	5.2 lbs
DIMENSIONS	11 - 7/8"(H) x 5"(W) x 10 - 7/8"(L)
LOAD CAPACITY	400 nails
OPERATING PRESSURE	70 - 100 psi (Regulator)
AIR CONSUMPTION	0.05 ft ³ / cycle (100 psi operating pressure)

STAPLES APPLICABLE



The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.

MAX USA CORP.
 257 East 2nd Street Mineola, NY 11501
 TEL: 800-223-4293 FAX: 516-741-3272
 www.maxusacorp.com



Dealer