

MAX

TWINTIER[®]



RB401T-E *STAND-UP*
BATTERY POWERED REBAR TYING TOOL

FEATURES/BENEFITS

1 REDUCES BACK STRAIN

The RB401T-E is an ergonomic solution for backbreaking slab work.

2 ADJUSTABLE HANDLES

Users can adjust the handles to 2 positions, to find the most comfortable fit for their height.

3 TRIGGERLESS TECHNOLOGY

An automatic contact mechanism (Pat. Pending) allows the tool to instantly tie when pushed down over a rebar intersection.

4 SHORTER TIE HEIGHT

A Wire Bending Mechanism (Pat. Pending) produces a shorter tie height. Less concrete is needed to fully cover a wire tie.

5 TILT SENSOR

The tilt-sensor prevents the tool from tying when angled upward.

6 ENCLOSED DESIGN

Greater protection against debris and moisture entering the tool.

RB401T-E




7 QUICKLY & EASILY LOAD TIE WIRE

Rapidly load the dual wire coil with the quick load magazine design.

* Requires at least 2" clearance between chaired rebar and the ground. For smaller clearance, down to 1-1/8", please use the short nose attachment. This specification varies by rebar combination.


MULTIPLE REBAR COMBINATIONS



3 Bar Combinations

Maximum

#7 x #4 x #4
(22mm x 13mm x 13mm)



4 Bar Combinations

Maximum

#4 x #4 x #4 x #4
(13mm x 13mm x 13mm x 13mm)

TW1061T TIE WIRE SERIES



19 ga. Steel Wire



19 ga. Poly Coated Wire



19 ga. Electro. Galvanized Wire



19 ga. Buy American Wire

TW1061T-S- STAINLESS STEEL WIRE IS ALSO AVAILABLE AS A SPECIAL ORDER ITEM.

TOOL SPECIFICATIONS

Weight	10.2 lbs
H x W x L	12- 3/4" x 16" x 43-3/8"
Tying Speed	Approx. 1/2 sec.
Rebar Capacity	#3x#3 to #6x#6
Wire Series	TW1061T
Wire Diameter	19 ga.
Ties Per Coil	Approx. 155 to 260
Ties Per Charge	Approx. 4000
Coils Per Box	30
Battery	JPL91440A
Voltage	DC 14.4 V
Recharge Time	Approx. 65 minutes full charge (50 minutes 80%)
Standard Equipment	Battery, Charger, Nose Attachments* Hard Plastic Carrying Case, and Hex Wrench. (2 Spare bolts are included, for changing the nose attachment)

APPLICATIONS ▶▶

Commercial Buildings | Foundations | Road and Bridge Construction
Water Treatment Tanks | Basements | Water Retaining Structures

MAX

MAX USA CORP.

205 Express St, Plainview NY 11803

800-223-4293

www.maxusacorp.com

PROUDLY DISTRIBUTED BY: